

Product designation

Picolite small lamp

article no. 32.021.00

Product description

Small lamp with built-in reflector. Small dimensions and little weight for tabletops and mobile work. Plug-in flash tube 1600 J / 5900 K with spring fastener. Own accessories with small dimensions. Using the Pulso adapter, lightweight reflectors and accessories from the Pulso assortment may be applied. Switch and fuse for modelling lamp. Built-in tilt head with adjustable lever and umbrella holder. Fan for long series of flashes. Suitable for use with 100 V – 240 V voltages due to the stabilized supply voltage for the cooling fan. Thermal protection. The protecting glass 5500 K is UV-coated and available in 5500 K as well as “clear” or “mat”. Handle. Max. 1600 J. Compatible with the battery-operated power pack Mobil A2R (without modelling light when operating with battery).

Scope of delivery

Lamp equipped with flash tube 1600 J / 5900 K, integrated protecting glass 5500 K and halogen modelling lamp.

Protection cap, cable 3.5 m / 11.5 ft

Technical data

Flash energy	max. 1600 J
f-stop at 2 m (6 ½ ft.) distance, 100 ISO	1200 J: 22 4/10 with lamp angle 130° 1600 J: 22 9/10 with lamp angle 130°
Modelling light (fuse value)	150 W Halogen (3.15 AF)
Length of cable	3.5 m (11.4 ft.)
Cooling	fan stabilized
Dimensions	overall 205 x 135 mm / 8.1 x 5.3 inches diameter 80 mm / 3.1 inches
Weight with cable	1.25 kg / 2.7 lb
Stand adapter	for bolts broncolor and Manfrotto 16 mm (0.6 inch)

Accessories

Attachment with 3 honeycomb grids and 2 aperture plates to Mobilite, Mobilite 2 and Picolite art. no. 33.204.00

Barn door with 4 wings to Mobilite, Mobilite 2 and Picolite	art. no. 33.244.00
Pulso adapter to Mobilite 2 and Picolite	art. no. 33.501.00
Fresnel spot attachment to Picolite and Mobilite 2	art. no. 33.631.00
Halogen modelling lamp 230 V / 150 W to Picolite	art. no. 34.201.00
Halogen modelling lamp 120 V / 150 W to Picolite	art. no. 34.202.00
Flash tube 1600 J without UV-coating to Mobilite 2 and Picolite	art. no. 34.308.00
Protecting glass 5500 K to Mobilite 2 and Picolite	art. no. 34.332.00
Protecting glass 5500 K, mat, to Mobilite 2 and Picolite	art. no. 34.335.00
Twin articulated arm to Mobilite 2 and Picolite	art. no. 35.102.00
Stand clamp for twin articulated Picolite/Mobilite 2 adapter to Satellite Evolution	art. no. 32.912.00 art. no. 35.214.00
Picobox	art. no. 33.128.00

Compatibility

Power packs	Grafit 2, 4, A2, A4, A2 RFS, A4 RFS, A8 RFS, A2 plus, A4 plus, Nano 2, Mobil A2R, Primo, Primo A, Primo A fashion, Primo 4, Pulso 2, A2, 4, A4, Opus 2, A2, 4, A4, A8, 304, 404 Server
Pulso accessories (with help of adapter)	P70, P65, P50, P45, P-Travel, conical snoot, P-soft, softlight reflector, Mini-Hazylight, Cumulite 2, Megaflex, broncolor Flooter, Pulsoflex up to 80 x 80 cm (31.5 x 31.5 inch), Satellite Evolution (with adapter), all umbrellas
without adapter	Fresnel spot attachment, honeycomb, Spot attachment, Picobox

Special features

- For safety reasons, never operate the lamps without the protecting glass in place.
- The accessories are identical with those of the Mobilite 2.